

- Contactless design – Inductive technology
- Wear-free operation
- Stroke lengths up to 1000mm
- 5.4mm body diameter
- Absolute measurement
- Infinite resolution
- High temperature capability – Up to 200°C or down to -55°C
- Working pressures up to 670Bar
- Separate signal conditioning (EICT)
 - High performance driver circuit
 - Zero and span adjustment
 - Choice of enclosure designs



The ICT080 Contactless In-Cylinder Linear Transducer has been specifically designed for smallbore, mobile and static hydro-pneumatic actuators

Designed primarily for the off-highway markets, the ICT080 linear transducer provides reliable, fit-andforget position sensing of the cylinder rod in actuators with strokes up to 1000mm, with a body diameter of only 8mm.

It is a robust, non-contact transducer suitable for the harsh conditions of lifting and steering position applications and hydro-pneumatic active suspension systems. It works on an inductive coil principle, with virtually infinite resolution and is capable of withstanding temperatures down to -55°C and up to +200°C, with working pressures to 670Bar (10,000psi).

The EICT signal-conditioning module has been specifically designed to operate with the Penny and Giles range of SLT and ICT contactless linear position transducers

The module incorporates a high performance circuit that drives the transducer and provides a choice of output signals with zero and span adjustment for simple user configuration. The module can be supplied in a choice of enclosures, with sealing to IP66 or IP68 protection.

SPECIFICATIONS

ELECTRICAL

MEASUREMENT RANGE	Maximum stroke selectable up to 1000mm
SENSOR RESOLUTION	Infinite
SENSOR TEMPERATURE COEFFICIENT	<±100ppm of electrical stroke /°C (+20°C to +60°C) <±200ppm of electrical stroke /°C (-20°C to +100°C) <±300ppm of electrical stroke /°C (-20°C to +200°C)

MECHANICAL

MAXIMUM SENSOR WORKING PRESSURE	670Bar
---------------------------------	--------

ENVIRONMENTAL

SENSOR TEMPERATURE RANGE	Operating: Refer to ordering code Storage: -55°C to +200°C
ELECTROMAGNETIC INTERFERENCE	EN61000-6-2, 100V/m (EICTM adjacent to transducer) Derangement <0.05% FS EN61000-6-2, 10V/m (EICT 1m cable to transducer) Derangement <0.05% FS
